

10 of the building and wherein said single member defines a cornered inner surface  
11 adapted for contacting the building and a spaced apart cornered outer surface parallel  
12 to said cornered inner surface adapted for contacting the corner post;  
13 a first support member flange lying in the first plane and extending  
14 outwardly from said first portion a predetermined distance and extending  
15 continuously along the entire length of said first portion and from said cornered inner  
16 surface radially outwardly; and  
17 a second support member flange lying in the second plane and  
18 extending outwardly from said second portion a predetermined distance and  
19 extending continuously along the entire length of said second portion[, wherein said  
20 first and second support member flanges extend] and from said cornered inner  
21 surface radially outwardly.

1 2. (Twice Amended) The support and insulating member of claim 1  
2 wherein said:  
3 support and insulating member is fabricated from a material having  
4 insulating qualities.

1 3. (Twice Amended) The support and insulating member of  
2 claim 2 wherein said material is selected from the group consisting of expanded,  
3 extruded or molded polystyrene foam plastic.

1 4. (Twice Amended) The support and insulating member of  
2 claim 1 wherein the support and insulating member has a length and thickness  
3 adapted for corresponding to and for filling the hollow space between the corner post  
4 and the external wall of the building along the entire length of the corner of the  
5 building.

Please add new claim 5 as follows:

1 5. (New) An insulating support comprising:  
2 a single support member having first and second portions angularly  
3 disposed from each other, said first and second portions defining a cornered inner